

**Firestop mortar CP 636**



**Applications**

- Permanent firestopping of cables, cable trays, and non-combustible pipes in medium to large wall and floor openings
- Single, multiple and mixed penetrations
- Medium to large multiple penetrations in concrete and masonry in combination with other products

**Advantages**

- Excellent application characteristics
- Easy to install with trowel or commercially available pumps thanks to adjustable consistency
- High yield Stiff (forms not always required)
- Contains no asbestos, phenol or halogen constituents
- Good adhesion to steel, concrete, and masonry



**Technical data**

<b>Base materials</b>	Concrete, Masonry
<b>Intumescent</b>	No
<b>Max. compressive strength after 28 days</b>	2.9 N/mm <sup>2</sup>
<b>Re-penetration</b>	Possible
<b>Application temperature range</b>	5 - 80 °C
<b>Reusable (and removable)</b>	Not possible
<b>Setting time (approx.)</b>	10 h
<b>Approvals</b>	ETA
<b>Working time (approx.)</b>	45 min
<b>Temperature resistance range</b>	-10 - 80 °C



Firestop Systems and Construction Chemicals

<b>Ordering designation</b>	<b>Sales pack quantity</b>	<b>Item number</b>
CP 636 20KG	1 pc	334897

Please visit our website for the latest item numbers and related products.